

GP Batteries

PRODUCT SPECIFICATION

GP SafeGuard Hybrid Product Model: LSS7H

Revision History

Revision	Date	Initiator	Reason for Change
0.0	08 Feb 2018	CC Li	New release

Prepared By	Approved By
CC Li	Kevin Chan
08 Feb 2018	08 Feb 2018





GPI International Limited

7/F, Building 16W, 16 Science Park West Avenue
Hong Kong Science Park, New Territories, Hong Kong,
Tel: (852) 2484 3333 Fax: (852) 24805912
Email: gpi@goldpeak.com
Website: <http://www.gpbatteries.com>

GP Batteries

Product Specification

Model no.: LSS7H



Product Name : GP Safeguard Hybrid RF3.1H
Description : Cordless safety and security LED sensor light, one headlamp, LSS7H

Electrical characteristics

Input Voltage : 4.5VDC (3 x 1.5V AA batteries) / 3.7VDC (1 x Li-ion 18650 2600 mAh battery)
Operating Voltage : 3.7 - 4.5V
Maximum Wattage : 3.0W
Battery life time (Alkaline) : 600 days* (Based on 5 operation per day in Auto mode)
300 days* (Based on 10 operation per day in Auto mode)
200 days* (Based on 15 operation per day in Auto mode)
8 hours* (Constant On mode)
Battery life time (Li-ion) : 200 days* (Based on 5 operation per day in Auto mode)
100 days* (Based on 10 operation per day in Auto mode)
66 days* (Based on 15 operation per day in Auto mode)
2 hours* (Constant On mode)

Product Specification

Model no.: LSS7H

Lighting characteristics

CCT	: 4500K-5500K
CRI	: ≥ 80
luminous flux / Intensity	: ≥ 130 lm
LED type	: 1 x SMD LED
Light modes	: OFF / ON / AUTO
Light duration in auto mode	: 10 s \pm 3 s
Illuminated area at 2M height	: 1.2 M ²
Illuminated area at 4M height	: 5 M ²
Beam angle	: 35° \pm 5°

Sensors characteristics

Sensor	: Photo sensors & PIR Sensors
Sensor detection range	: 8M, 110°
Log in lux value	: 0-35 Lux (0- ∞ adjustable)
Log out lux value	: 0~40 Lux (0- ∞ adjustable)
Warm up time	: 30 s \pm 10 s

Physical characteristics

Operating temperature	: -20 °C to 50 °C
Storage temperature	: -20 °C to 50 °C
Dimension of Safeguard	: 96.0 (L) x 201.1 (H) x 129.9 (D) mm
Dimension of solar panel	: 85.0 (L) x 134.0 (H) x 77.5 (D) mm
Weight of Safeguard	: 250 g
Weight of solar panel	: 175 g
Cable length	: 3 m
(Between Safeguard & solar panel)	
Housing material	: PC
IP Rating	: IP55

Product compliance	: CE, Rohs
Warranty Period	: 12 months from ex-factory date